

## Rutland Stove Polish

Item 70

- Preserves and restores the beauty of cast iron and steel
- Can be buffed to a dark lustrous glow
- Made with the highest quality waxes and blackest pigments



### Description:

Rutland non-flammable paste stove polish is a blend of the highest quality waxes emulsified with the blackest pigments. It is used to preserve and restore the beauty of cast iron and steel.

### Performance Characteristics:

- Non-flammable
- Easy to use

### Recommended Uses:

It may be used on cast iron or steel. It preserves the metal on new stoves and helps prevent rust. If used on old rusty stoves it will renew and re-black the surface and help prevent further deterioration. It may be used on grills, ornamental iron work and fences wherever a rich shiny glow is desired. It is especially recommended for preserving heating equipment stored out of season. Please refer to the limitation section of this document.

### Preparation:

Check that the fire is completely extinguished and that all surfaces are cold to the touch. Wear protective gloves to keep hand clean. Test on a small inconspicuous place to observe the effect.

### Application:

Squeeze a small amount onto a cold surface. Spread over the surface with a damp cloth or sponge. Let dry about 10-15 minutes or until it looks dry. Buff to the desired glow with a soft dry cloth. When firing the stove for the first time after applying

polish, ventilate the house, as heated waxes in the Stove Polish may emit fumes.

### Clean up:

Clean polish from skin with diluted chlorine bleach.

### Typical Physical Properties:

Solvent	Water
Weight/Gallon	10 lb.
Consistency	Paste
Flashpoint	N/A
Dry Time	10-15 minutes before buffing
Color	Black
Storage/Handling	Wear gloves to avoid stains Do not store below freezing

### Limitations:

The first firing of the stove will cause smoke to be emitted. Normally this will last 10-15 minutes, but this depends on how heavily the polish was applied. Stove Polish can not be thinned as it would break the emulsion. Do not apply to painted surfaces as the polish will not penetrate the paint layer. It will not adhere to or blacken sandblasted surfaces; we recommend painting them. Not recommended on areas that would come into contact with food.

### Warranty and Limited Remedy:

This product will be free from defects in material and manufacture for a period of eighteen (18) months from date of manufacture. Rutland Fire Clay Company makes no other warranties including, but not limited to, any implied warranty of

merchantability or fitness for a particular purpose. User is responsible for determining whether the Rutland Fire Clay Company product is fit for a particular purpose and suitable for user's application. If this Rutland Fire Clay Company product is defective within the warranty period stated above, your exclusive remedy and Rutland Fire Clay Company's sole obligation shall be, at Rutland Fire Clay Company's option, to replace the Rutland Fire Clay Company product or refund the purchase price of the Rutland Fire Clay Company product.

**Limitation of Liability:**

Except where prohibited by law, Rutland Fire Clay Company will not be liable for any loss or damage arising from this Rutland Fire Clay Company product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

**CAUTIONS:**

**Irritant to eyes. If contact with eyes, flush with water for at least 15 minutes. Consult an eye doctor. Skin contact will produce staining. Wash with soap and water and rinse with diluted chlorine bleach to remove staining. Ingestion may produce gastrointestinal upset. Do not induce vomiting, but drink water. Get medical attention. Inhalation of large concentrations of wax vapor may produce headaches. Remove to fresh air. If discomfort persists, get medical attention.**

**KEEP OUT OF REACH OF CHILDREN  
EYE IRRITANT  
DO NOT INGEST**