

Gas log Soot Remover

Item 570-6

- Safely removes soot buildup from gas logs
- Instantly makes gas logs look like new
- Easy to use

Description:

A powerful spray-on cleaning treatment that quickly removes soot build-up from gas logs

Performance Characteristics:

- Will not clog gas orifices
- Will not harm burner or discolor logs
- Can not be overused.

Recommended Uses:

Use on vented and vent free gas log sets.

Surface Prep:

Turn on gas and allow enough time for the gas logs to become hot, approximately 15 minutes. Then turn off gas before applying Gas Log Soot Remover.

Application:

An effective treatment requires that the logs be hot. Set spray nozzle to mist setting. Be sure logs are red hot and the gas is turned off. Only use the stream setting to reach confined areas. Spray Gas Log Soot Remover directly on hot gas logs at the site of the soot build-up. Soot will fall off. After spraying, do not wipe the logs. No waiting period necessary before re-lighting the gas logs. Excessive or heavy accumulations of soot may require an additional spray treatment. If dark stains persist, test a spot and clean with a 50-50 mixture of white vinegar and hydrogen peroxide. *Do not use Gas Log Soot Remover on white birch gas logs.*



Clean up:

Wipe up spills and excess immediately with a damp cloth or sponge. Rinse textiles with water.

Typical Physical Properties:

Weight/Gallon	8.25 lbs.
Consistency	Liquid
Flashpoint	>200°F. TOC
Color	Light pink to clear
Storage/Handling	Store in cool place and away from sources of ignition

Limitations:

Do not use on white birch gas logs, including “birch”. Not effective on lightweight fiber logs. Do not spray on glass. Gas Log Soot Remover is not meant to replace regular maintenance.

Warranty and Limited Remedy:

This product will be free from defects in material and manufacture for a period of eighteen (18) months from date of manufacture. Rutland Fire Clay Company makes no other warranties including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose. User is responsible for determining whether the Rutland Fire Clay Company product is fit for a particular purpose and suitable for user’s application. If this Rutland Fire Clay Company product is defective within the warranty period stated above, your exclusive remedy and Rutland Fire Clay Company’s sole obligation shall be, at Rutland Fire Clay Company’s option, to replace the Rutland Fire Clay Company product or refund the

purchase price of the Rutland Fire Clay Company product.

Limitation of Liability:

Except where prohibited by law, Rutland Fire Clay Company will not be liable for any loss or damage arising from this Rutland Fire Clay Company product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

CAUTIONS:

Use with adequate ventilation. Avoid inhalation of vapors. Avoid contact with eyes and skin. Wear safety glasses and rubber gloves. In case of contact, flush eyes with water for 15 minutes and get medical attention. Wash skin with water. If irritation persists, get medical attention. Do not take internally.

**KEEP OUT OF REACH OF CHILDREN
EYE, SKIN AND THROAT IRRITANT
DO NOT TAKE INTERNALLY**