

Pipe Insulating Cement

Item #623, 624

- Conserves thermal energy
- Does not require heat to cure
- Asbestos free

Description:

An easy to use insulating cement that forms a trowelable paste when mixed with water.

Performance Characteristics:

- Suitable for temperatures up to 300°F
- Adheres to masonry or metal
- May be painted when dry

Recommended Uses:

Use to insulate pipes, fittings, tanks and boilers, to conserve energy.

Surface Prep:

Surfaces to be covered must be free from dirt, rust or oil.

Application:

We recommend the use of gloves, safety glasses and dust mask. Pour the Pipe Insulating Cement into water and mix thoroughly. Use equal parts by weight, such as 2 lb. dry mix with 2 pints of water. Spread the cement mixture with a trowel on the surface to be insulated. Apply to 1/2" or desired thickness. Do not press water out of cement, as it will lessen the coverage and insulating efficiency.

Coverage:

A 2 lb. container will cover approximately 2 sq. ft. 1/2" thick.

Clean up:

Clean up with water immediately.



Typical

Properties:

Consistency

Flashpoint

Tooling Time

Dry Time

Color

Storage/Handling

Physical

Dry mix

N/A

15 minutes

Approximately 24 hours, depending on temperature and humidity

Buff

Keep dry until used

Limitations:

Not for outdoor use. Keep unused material dry.

Warranty and Limited Remedy:

This product will be free from defects in material and manufacture for a period of eighteen (18) months from date of manufacture. Rutland Fire Clay Company makes no other warranties including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose. User is responsible for determining whether the Rutland Fire Clay Company product is fit for a particular purpose and suitable for user's application. If this Rutland Fire Clay Company product is defective within the warranty period stated above, your exclusive remedy and Rutland Fire Clay Company's sole obligation shall be, at Rutland Fire Clay Company's option, to replace the Rutland Fire Clay Company product or refund the purchase price of the Rutland Fire Clay Company product.

Limitation of Liability:

Except where prohibited by law, Rutland Fire Clay Company will not be liable for any loss or damage arising from this Rutland Fire Clay Company

product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

CAUTIONS:

May be irritating to skin, eyes, and respiratory tract. Wear appropriate gloves, safety glasses

and NIOSH approved dust mask. Wash skin with soap and water. In case of eye contact, flush with water for at least 15 minutes. If irritation persists, get medical attention. If ingested, consult a physician.

KEEP OUT OF REACH OF CHILDREN

06/01/06